



Dissociation and Recombination Effects on the Performance of Pulse Detonation Engines

Louis A. Povinelli
Glenn Research Center, Cleveland, Ohio

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at 301-621-0134
- Telephone the NASA Access Help Desk at 301-621-0390
- Write to:
NASA Access Help Desk
NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076



Dissociation and Recombination Effects on the Performance of Pulse Detonation Engines

Louis A. Povinelli
Glenn Research Center, Cleveland, Ohio

Prepared for the
16th International Symposium on Airbreathing Engines
sponsored by the International Society for Airbreathing Engines
Cleveland, Ohio, August 31–September 5, 2003

National Aeronautics and
Space Administration

Glenn Research Center

This report is a preprint of a paper intended for presentation at a conference. Because of changes that may be made before formal publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22100

Available electronically at <http://gltrs.grc.nasa.gov>

DISSOCIATION AND RECOMBINATION EFFECTS ON THE PERFORMANCE OF PULSE DETONATION ENGINES

Louis A. Povinelli*

National Aeronautics and Space Administration
Glenn Research Center
Cleveland, Ohio 44135

Abstract

This paper summarizes major theoretical results for pulse detonation engine performance taking into account real gas chemistry, as well as significant performance differences resulting from the presence of ram and compression heating.

An unsteady CFD analysis, as well as a thermodynamic cycle analysis was conducted in order to determine the actual and the ideal performance for an air-breathing pulse detonation engine (PDE) using either a hydrogen-air or ethylene-air mixture over a flight Mach number range from 0 to 4. The results clearly elucidate the competitive regime of PDE application relative to ramjets and gas turbines.

Introduction

Many excellent reviews of PDE's have been published^{9,10} and it is not our intent to review that literature. Instead, we will adopt a somewhat narrow point of view and limit this discussion to our previous work on *real gas chemistry and heating effects due to compression*.

a. Sensible Heat Release

In our previous work¹ we have shown the importance of real gas chemistry in detonation propulsion devices. A significant decrease in the sensible heat available for thrust was found to occur in PDE propulsion systems due to high temperature dissociation. A subsequent analysis² was carried out to compare the specific thrust, fuel consumption and impulse for a ramjet, a turbine engine (with variable amounts of mechanical compression) and a pulse detonation engine, as a function of flight Mach number. In that study, it was found that a PDE could provide comparable performance with a ramjet over a range of Mach numbers. Relative to the turbojet, however, the PDE was competitive only when the turbojet's mechanical compression was very low, of the order of 4.

b. Species Recombination

Subsequent to the studies mentioned above, CFD analyses were performed for an open ended detonation tube³. The computation, which included finite rate chemistry effects, showed that some recombination occurred in the burning gases behind the detonation wave. The recombination served to decrease the amount of sensible heat loss that occurs during the detonation process.

c. Performance Calculations

In a later paper⁴, the sensible heat release obtained from a finite rate CFD analysis was used to compute the impulse in an open-ended detonation tube. The same heat release was then used in a thermodynamic cycle code to calculate impulse. The difference in the two impulse values was assumed to represent the additional maximum potential performance attainable in a PDE. Those results were compared with experimental impulse data, which indicated a potential performance gain in specific impulse of 200 to 300 seconds.

Most recently, we have computed the performance of a hydrocarbon-air PDE over a wide Mach number range to demonstrate the potential usage in a combined cycle accelerator⁵.

Approach for the Comparative Analyses of Cycle Performance

a. Fundamental Considerations

The advantage of the pulse detonation engine (PDE) cycle over the Brayton cycle has usually been attributed to the higher thermodynamic efficiency of the PDE. This cycle advantage is normally depicted as a plot of thermal efficiency versus relative inlet temperature ratio, where the atmospheric temperature is used as the reference. The typical plot, shown in figure 1, assumes that a comparison of the different cycles is performed at a constant value of the temperature ratio, regardless of the type of cycle and the flight conditions. In addition, the heat release for all of the engine cycles is assumed

* Chief Scientist, Turbo Machinery and Propulsion Systems Division

to be equal. The usual result from figure 1, therefore, would show that at a temperature ratio of 2, the cycle efficiency for the PDE is 0.63, while that for a Brayton cycle is only 0.5. There are two fallacies associated with this type of comparison; namely (I.) the temperature ratio, T_3/T_0 (where T_0 is the atmospheric temperature), entering the combustor of a pulse detonation engine or a ramjet is lower than that of the gas turbine, and (II.) the available heat released in the detonation cycle is lower than that in a Brayton (either gas turbine or ramjet) cycle. In this paper, we shall examine both of these issues in some detail, in order to establish an improved comparative basis for the propulsion performance of each of the cycles. Some typical flight conditions will be assumed in order to demonstrate the effects mentioned above.

b. Inlet/Compressor Temperature Rise

In regards to issue (I.), the PDE and the ramjet utilize only *ram* compression and heating to increase the inlet temperature ratio, T_2/T_0 , where T_0 is the atmospheric or reference temperature and T_2 is the temperature of the air exiting the inlet and diffuser section of the engine. In the case of the gas turbine, the ram compression is further boosted by the *mechanical* compressor (and fan) to a temperature T_3 that is higher than that in the PDE or ramjet. In order to compare the relative performances, it is necessary, therefore, to use the value of the temperature, T_2 , entering the PDE detonation chamber (or into the ramjet combustion chamber) as well as the higher temperature, T_3 entering the gas turbine combustion chamber. ***The effect of using these temperatures is to shift the comparison point between the PDE (and the ramjet) and the gas turbine cycles to different locations on the abscissa of figure 1.***

Therefore, the cycle comparison in figure 1 must be modified so that the PDE efficiency comparison is now made with the corrected (or higher temperature ratio) gas turbine efficiency. The value of the higher temperature ratio for the turbine depends on the amounts of mechanical compression. For example, if the specific heat ratio is 1.4 and the flight speed is Mach 1, then the ram temperature ratio value is 1.2. If the mechanical compression ratio is 2, the resulting temperature ratio is 1.49. This means that if the comparison point for cycle efficiency was at a temperature ratio of 1.2 for the PDE (upper square symbol in figure 1), then the temperature ratio for the gas turbine should be at 1.49 (lower square symbol in figure 1, rather than the lower triangular symbol).

The paper presents results for the propulsion performance parameters, i.e., specific thrust, impulse and specific fuel consumption as a function of flight Mach numbers, accounting for the correct inlet temperatures as well as real gas effects, which are described in the next section.

c. Sensible Heat Availability

In regards to issue (II.), it has been shown that the ***higher temperatures associated with the detonation process creates a greater amount of dissociated species and lower sensible heat release than does the deflagration process in a ramjet or gas turbine engine.*** Figures. 2 and 3 show previous results considering only dissociation losses.

Use of a time accurate CFD code including finite rate chemistry has been used to determine the combined dissociation and recombination occurring in an open-ended PDE tube. The resulting effect on the amount of sensible heat available for creating thrust is significant and, in fact, causes the specific thrust, impulse and fuel consumption values for the PDE to become inferior to the gas turbine at some conditions, as shown in figure 2.

d. Ethylene-air Computations

Our goal is to determine the real gas effects on performance with a typical hydrocarbon-air mixture, over a Mach number range with the additional requirement of proper accounting for ram and compression heating effects.

In order to determine the sensible heat available for the PDE, an unsteady CFD method⁶ was used in ref. 7 was used to determine the value of the sensible heat release including both dissociation and recombination. The resulting value was then used in the thermodynamic cycle analysis⁸ to determine the specific thrust, fuel consumption and impulse for a range of Mach numbers.

It is noted that the short mechanism of ref. 11 was used in order to enable reasonable computational time.

e. Validation of Analysis Methods

The impulse results for the thermo cycle analysis and the CFD results for hydrogen-air mixtures are compared with experimental data in figure 4. The agreement provides us with some measure of confidence in our approach. The cycle results are considered to be the ideal whereas the lower impulse CFD values reflect the actual conditions occurring in the experimental tests.

Results

a. Specific Thrust

The results are shown in figure 5 for stoichiometric ethylene-air for Mach numbers from 0 to 5, accounting for the correct inlet/compressor temperatures and for dissociation and recombination. It is seen that the PDE performance exceeds that of a ramjet out to a value of about Mach 3.5, and is equivalent to that of a turbojet at the same point.

b. Specific Fuel Consumption

The specific fuel consumption of the PDE is less than the ramjet out to about Mach 2.5, and always slightly greater than the gas turbine, see figure 6.

The impulse of the PDE exceeds the ramjet out to Mach 3.5 and is then equivalent. In the case of the gas turbine, the impulse is greater out to Mach 2.5 and is then equivalent thereafter.

c. Impulse

It is noted that the value of the impulse from our thermo cycle analysis calculation is 2019 seconds at a temperature ratio of 1, and the maximum point from our unsteady CFD is 1962 seconds. The difference in the cycle value and the CFD represents a potential performance improvement.

d. Significance of Results

The overall significance of these results is that PDE's have a flight range over which they can be competitive from a theoretical propulsion viewpoint as shown above; namely as an alternative to ramjets with significant improvement over the entire Mach number range.

Two common fallacies in the comparison of propulsion power cycles have been discussed to some depth in this paper and the proper procedures for making relative comparisons were described.

The results described in this paper clearly establish two items having major technical significance on cycle performance:

- (1) the critical impact of real gas chemistry on the performance of PDE's and
- (2) the need to differentiate between the PDE and Brayton cycles in establishing the correct initial temperature condition which accounts for both ram and compression heating.

References

1. Povinelli, Louis A., "Impact of Dissociation and Sensible Heat Release on Pulse Detonation and Gas Turbine Engine Performance", NASA/TM—2001-211080, July 2001, also 15th ISABE Symposium Paper 2001-1212, Sept 2002.
2. Povinelli, Louis A., Lee, Jin-Ho and Anderberg, Michael O., "Role of Air-Breathing Pulse Detonation Engines in High Speed Flight", NASA/TM—2001-211163, Sept 2001, also 52nd IAF Congress Paper IAF-01-S.5.01, Oct. 2001.
3. Povinelli, Louis A. and Yungster, Shaye, "Airbreathing Pulse Detonation Engine Performance", NASA/TM—2002-211575, May 2002, 26th Air-breathing Propulsion Subcommittee, JANNAF Conference, Destin, FL, April 8-12, 2002.
4. Povinelli, Louis A. and Yungster, Shaye, "Thermodynamic Cycle and CFD Analyses for Hydrogen Fueled Air-Breathing Pulse Detonation Engines", NASA/TM—2002-211698, June 2002, also AIAA Paper 2002-3629, 38th AIAA/ASME/SAE/ASEE Joint Propulsion Conference, Indianapolis, Indiana, July 7-10, 2002.
5. Povinelli, Louis A., "Pulse Detonation Engines for High Speed Flight", Paper 17-5169, 11th International Conference of the AIAA/AAAF Hypersonics Conference, Orleans, France, Sept 29-Oct. 2002. Also NASA/TM—2002-211908, Sept. 2002.
6. Yungster, S. and Radhakrishnan, K., "A Fully Implicit Time Accurate Method for Hypersonic Combustion: Application to Shock Induced Combustion Instability", *Shock Waves*, Vol. 5, 1996, pp. 293-303.
7. Povinelli, Louis A. and Yungster, Shaye, "Real Gas Effects on the Performance of Hydrocarbon-Fueled Pulse Detonation Engines", AIAA Paper 2003-0712, 41st Aerospace Sciences Mtg. & Exhibit, 6-9 January 2003, Reno, NV.
8. Heiser, W. and Pratt, D., "Thermodynamic Cycle Analysis of Pulse Detonation Engines", *Jrl. of Propulsion and Power*, Vol. 18, No. 1, Jan-Feb 2002.
9. Bussing, T. and Pappas, G., "Pulse Detonation Engine Theory and Concepts", in Developments in High-Speed-Vehicle Propulsion Systems, Edited by S.N.B. Murthy and E.T. Curran, AIAA Progress in Astronautics and Aeronautics, Vol. 165, 1966.
10. Kailasanath, K. and Patnik, G., "Performance Estimates of Pulse Detonation Engines", 28th International Symposium on Combustion, Edinburgh, Scotland, 2000.

11. Li, S.C., Varatharajan, B. and Williams, F.A., "The Chemistry of Ethylene Ignition for Application to Pulse detonation Engines", AIAA Paper 2000-3475, Joint Propulsion Conference, July, 2000, Huntsville, AL.




Figure 1.—Thermal efficiency for the PDE and Brayton Cycles, stoichiometric propane-air. Significance of symbols discussed in text.




Figure 2.—Specific thrust for the PDE and Brayton cycles, stoichiometric propane-air.




Figure 3.—Specific thrust versus Mach number for Brayton and PDE cycles, stoichiometric propane-air, numbers on plot represent the Brayton mechanical compression ratio, dissociation losses only, flight at 33K feet.




Figure 4.—Comparison of analyses with Wright Labs data, hydrogen-air.




Figure 5.—Specific thrust versus Mach number including real gas effects of dissociation and recombination, stoichiometric ethylene-air, flight at 33K feet.




Figure 6.—Specific fuel consumption for conditions in figure 5.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 2003		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE Dissociation and Recombination Effects on the Performance of Pulse Detonation Engines			5. FUNDING NUMBERS WBS-22-719-10-01	
6. AUTHOR(S) Louis A. Povinelli				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-14104	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA TM-2003-212538 ISABE-2003-1216	
11. SUPPLEMENTARY NOTES Prepared for the 16th International Symposium on Airbreathing Engines sponsored by the International Society for Airbreathing Engines, Cleveland, Ohio, August 31-September 5, 2003. Responsible person, Louis A. Povinelli, organization code 5000, 216-433-5818.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Categories: 07, 28, and 37 Available electronically at http://gltrs.grc.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 301-621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This paper summarizes major theoretical results for pulse detonation engine performance taking into account real gas chemistry, as well as significant performance differences resulting from the presence of ram and compression heating. An unsteady CFD analysis, as well as a thermodynamic cycle analysis, was conducted in order to determine the actual and the ideal performance for an air-breathing pulse detonation engine (PDE) using either a hydrogen-air or ethylene-air mixture over a flight Mach number range from 0 to 4. The results clearly elucidate the competitive regime of PDE application relative to ramjets and gas turbines.				
14. SUBJECT TERMS Detonations; Pulse detonation engines; Real gas effects			15. NUMBER OF PAGES 12	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	